

DMT Series TRUNNION Mounted DBB Modular VALVES - B/N/B

DESIGN FEATURES

ISOLATE VALVE :-

- * Firesafe Design to BS 6755 Pt 2
- * Wide choice of Flange Rating & ends.
- * Robust HIGH pressure Valve, DESIGNED to be maintained
- * Ball Valve has anti blowout stem for safety
- * Trunnion Mounted Ball design for positive shut-off
- * Floating Ball Styles Available
- * Replaceable seats & seals for extended life

VENT VALVE :-


- * NON-Rotating hard tip on bleed valve for effective shut-off
- * Back sealing on the stem & adjustable gland packing
- * Stem Seal below actuating threads to prevent contamination & gauling of threads
- * Metal/Metal bonnet seal for pressure tightness even at elevated temperatures

- * Choice of Block, Block & Bleed or Double Block & Bleed
- * Bleed Port with pressure plug or Tube fitting
- * Materials to NACE Specification & Full traceability




NS HEAD ASSY

ITEM	COMPONENT	MATERIAL
1	BODY	316 S 11
2	BONNET HOUSING	316 S 11
3	HANDLE	316 S 11
4	STEM	316 S 11
5	STEM TIP	17/4 PH
6	GRUB SCREW	STAINLESS STEEL
7	DUST CAP	PVC
8	RETAINING CAM	STAINLESS STEEL
9	RETAINING SCREW	STAINLESS STEEL
10	GLAND ADJUSTER	316 S 11
11	LOCK NUT	316 S 11
12	GLAND PACKING	RTFE / GRAPHOIL
13	BONNET GASKET	316 S 11
14	BONNET SEAL	V PTFE



ITEM	COMPONENT	MATERIAL
1	BODY	316 S 11
2	END FLANGE	316 S 11
3	BALL	316 S 11
4	STEM	316 S 11
5	STEM SEAL	PTFE/GRAPHOIL
6	SEATS	PTFE / PVDF/PEEK
7	TOP SEAL	RTFE/GRAPHOIL
8	END FLANGE SEAL	PTFE/GRAPHOIL
9	PIN	STAINLESS STEEL
10	LEVER HANDLE	STAINLESS STEEL
11	HANDLE SLEEVE	PVC
12	NUT	A4 ss
13	WASHER	A4 ss
14	SPACER	316 SS



DM TCM - BALL VALVE ASSY Block [Isolate] - Ball Style

Part No. DM TCM F1925CB3S

1"600lb Serrated Face Flanged Double Block & Bleed
Valve [Ball/Needle/Ball Configuration] with PTFE/17-4PH
Trim. 1/2"NPT Vent in316ss

VALVE PART NUMBER and ORDERING TABLE									
Series - Style	PRESSURE	BORE	Inlet Size/Type/Finish		Outlet Size/Type/Finish		Vent	Material	Options
DM TC	M	F = Flange Rating	08	A=C150 B=C300 C=C600 D=C800 E=C900 F=C1500 G=C2500	A= Smooth B= Serrated C=RTJ H=HUB	08	A=C150 B=C300 C=C600 D=C800 E=C900 F=C1500 G=C2500	A= Smooth B= Serrated C=RTJ H=HUB	1=1/4"NPT 2=1/4BSPP 3=1/2"NPT 4=1/2BSPP 5=3/4"NPT 6=3/4BSPP 7=1"NPT 8=1BSPP
			10			10			
			15			15			
			20			20			
			25			25			
			32			32			
			40			40			
			46			46			
			50			50			
			54			54			
	=	B/N/B	32	A=C150 B=C300 C=C600 D=C800 E=C900 F=C1500 G=C2500	A= Smooth B= Serrated C=RTJ H=HUB	32	A=C150 B=C300 C=C600 D=C800 E=C900 F=C1500 G=C2500	A= Smooth B= Serrated C=RTJ H=HUB	A - All-Bronze C - C/Steel D - UNS31803 Y - UNS32750 U - UNS32760 H - Hastelloy I - Incoloy M - Monel S - 316 SS X - SPECIAL
			38			38			
			50			50			
			65			65			
			75			75			
			46			46			
			50			50			
			54			54			
			32			32			
			38			38			
			50			50			
			65			65			
			75			75			
			46			46			
			50			50			
			54			54			

We reserve the right to change specifications stated in this leaflet due to our continuing programme of development. All Ball valves have lever handle as standard. Anti-Tamper Keys are always supplied separately, for security. Ball & stem materials will be the same as the body material except for C/Steel which has 316 trim. It is always recommended that the valve is supported and not left to carry the weight of the pipe work as damage may occur.



Global Supply Line - Australia Colson agent & stockist
Contact us: sales@globalsupplyline.com.au, Website: www.globalsupplyline.com.au



Colson X-Cel Ltd, Park Works, Park Road, Elland,
West Yorkshire HX5 9HN United Kingdom
Tel: +44 (0) 1422 377 999 Fax: +44 (0) 1422 377 333
Web: www.colson.co.uk Email: sales@colson.co.uk